

2ND EDITION



# PAVER PATTERNS, BORDERS AND ACCENTING GUIDE.


PROFESSIONAL REFERENCE FOR LANDSCAPE ARCHITECTS,  
DESIGNERS, SPECIFIERS, BUYERS AND HARDSCAPE CONTRACTORS.

# PATTERNS


Mixing paver styles, shapes and colors along with contrasting borders and insets creates endless design opportunities to match your property's architecture and personality. Use these common paver, plank and slab patterns to help create the patio, walkway or driveway you'll be proud of.




## BARN PLANK LANDSCAPE TILES (not suitable for vehicular)




**Pattern 1:** 15.5 x 9.75" = 20.9%  
23.37 x 9.75" = 31.6%  
35 x 9.75" = 47.4%



**Pattern 2:** 15.5 x 9.75" = 20.9%  
23.37 x 9.75" = 31.6%  
35 x 9.75" = 47.4%




**Pattern 3:** 35 x 9.75" = 100%




**Pattern 4:** 35 x 9.75" = 100%




## SLATE LANDSCAPE TILES (not suitable for vehicular)




**Pattern 1:** 12 x 12" = 14%  
24 x 12" = 29%  
24 x 24" = 57%




**Pattern 2:** 12 x 12" = 14%  
24 x 12" = 29%  
24 x 24" = 57%



**Pattern 3:** 12 x 12" = 7.69%  
24 x 12" = 15.39%  
24 x 24" = 30.77%  
24 x 36" = 46.15%




**Pattern 4:** 12 x 12" = 11.1%  
24 x 12" = 11.1%  
24 x 24" = 44.4%  
24 x 36" = 33.3%




**Pattern 5:** 12 x 12" = 25%  
24 x 12" = 50%  
24 x 24" = 25%


## TRAVERTINE LANDSCAPE TILES (not suitable for vehicular)




**Pattern 1:** 12 x 24" = 22.26%  
18 x 24" = 33.33%  
24 x 24" = 44.4%




**Pattern 2:** 24 x 24"



**Pattern 3:** 12 x 24" = 22.26%  
18 x 24" = 33.33%  
24 x 24" = 44.4%




**Pattern 4:** 24 x 24" = 36.2%  
18 x 24" = 27.3%  
24 x 24" = 36.5%




**Pattern 5:** 24 x 24" Running Bond


## MINNETONKA, BARRINGTON AND ACCENT PAVERS (not suitable for vehicular)




**Pattern 1:** 8 x 16" = 16.6%  
16 x 16" = 33.33%  
16 x 24" = 50.7%




**Pattern 2:** 8 x 16" = 16.6%  
16 x 16" = 33.33%  
16 x 24" = 50.7%



**Pattern 3:** 8 x 16" = 16.6%  
16 x 16" = 33.33%  
16 x 24" = 50.7%




**Pattern 4:** 8 x 16" = 16.6%  
16 x 16" = 33.33%  
16 x 24" = 50.7%




**Herringbone:** 6 x 12" Accent  
(suitable for vehicular)


## MEZZANO, SERANO AND ACCENT PAVERS (suitable for vehicular)




**Pattern 1:** 5.7 x 5.7" = 14%  
5.7 x 11.5" = 29%  
11.5 x 11.5" = 57%




**Pattern 2:** 5.7 x 5.7" = 14%  
5.7 x 11.5" = 29%  
11.5 x 11.5" = 57%



**Pattern 2 with 6 x 12" sailor border**




**Pattern 2 with 6 x 12" double sailor border**




**6 x 12" Accent (running bond)**


**BROADMOUR PAVERS** (24 x 24 not suitable for vehicular)




**Pattern 1:** 6 x 12" = 14.3%  
12 x 12" = 28.57%  
24 x 12" = 57.14%




**Pattern 2** (square only)




**Pattern 3** (rectangle only)



**Pattern 4** (rectangle only)




**Pattern 5:** 12 x 12" = 20%  
24 x 24" = 80%




**Pattern 6** (rectangle only)


**BROADMOUR PLANK PAVERS** (not recommended for vehicular)



Herringbone




Running Bond




Parquet




**COBBLE STONE PAVERS** (suitable for vehicular)




**Pattern 1**




**Pattern 2**




**Pattern 3**



**Pattern 1: (one layer)**




**Pattern 2: (one layer)**




**Pattern 3: (one layer)**


**LAMONT PAVERS** (suitable for vehicular)




**Pattern 1:** 4 x 8" = 20%  
6 x 8" = 30%  
10 x 8" = 50%




**Pattern 2:** 4 x 8" = 12%  
6 x 8" = 19%  
10 x 8" = 31%  
12 x 8" = 38%



**Pattern 3:** 4 x 8" = 12%  
6 x 8" = 19%  
10 x 8" = 31%  
12 x 8" = 38%




**Pattern 4:** 6 x 8" = 45%  
10 x 8" = 55%




**Pattern 5:** 4 x 8" = 29%  
10 x 8" = 71%




**COLONIAL PAVERS** (suitable for vehicular)




**Pattern 1:** 6.3 x 6.3" = 25%  
6.3 x 9.4" = 75%




**Pattern 2:** 6.3 x 3.1" = 13.37%  
6.3 x 4.6" = 19.75%  
6.3 x 6.3" = 26.75%  
6.3 x 9.4" = 40.13%



**Pattern 3:** 6.3 x 3.1" = 14.81%  
6.3 x 6.3" = 29.63%  
6.3 x 9.4" = 55.56%




**Pattern 4:** 6.3 x 3.1" = 14.55%  
6.3 x 6.3" = 36.36%  
6.3 x 9.4" = 49.09%




**Pattern 5:** 6.3 x 3.1" = 13.37%  
6.3 x 4.6" = 19.75%  
6.3 x 6.3" = 26.75%  
6.3 x 9.4" = 40.13%




**HOLLAND PAVERS** (suitable for vehicular)




**Pattern 1**




**Pattern 2**




**Pattern 3**



**Pattern 4**




**Pattern 5**



**Pattern 6**

# ACCENTING AND BORDERS

Except for Broadmour 10cm, Holland-Eco and Cobble Stone 8cm pavers, Interlock pavers are all 6cm in height making them very designer and installer friendly.




## AMERICAN BRICK PAVER: Brown, Buff, Onyx and Tuscan Red (all KolorLast)




Basket




Double Sailor



Soldier with Sailor




## 6 X 12 ACCENT PAVERS: Brown, Buff and Onyx (all KolorLast)




Soldier Course




Double Sailor



Double Sailor with American Brick



## COLONIAL ACCENT: Brown, Buff and Onyx w/KolorLast




3/4 Square Sailor with 6 x 9 Soldier



6 x 9 Sailor with American Brick Sailor




3/4 Square Sailor with American Brick Sailor




3/4 Square Soldier with American Brick Sailor

Examples shown to scale with a 24" pavers.

**LAMONT 4 X 8 AND 6 X 8: Brown, Desert Buff and Onyx**




4 x 8 and 6 x 8 Soldier Courses




4 x 8 Double Sailor Course



4 x 8 Double Sailor with American Brick




6 x 8 Soldier with American Brick Sailor Course




6 x 8 Soldier with American Brick

**FLAGSTONE:**




6 x 8 Lamont Soldier with American Brick Sailor Course

American Brick Soldier



Flagstone Inlay with American Brick and 6 x 12 Accent



4 x 8 Lamont Double Sailor Course

6 x 12 Accent Soldier Course



## SLABS, PLANKS AND PAVERS.

Landscape paver/flooring types are defined by nationally accepted ASTM standards. These definitions are determined by their ratios of length to width, top surface area and thickness, and are used for appropriate product selection. Slabs are typically larger than a short/thicker paver, and planks are generally long and narrow. All pavers, slabs and planks are suitable for pedestrian traffic, but not for all applications - such as vehicular or pedestal use. Please note: before choosing or purchasing any landscape flooring product, be sure to consult a hardscape professional for appropriate product selection.

### DEFINITIONS:

#### ASTM C1782 Segmental Concrete Paving Slabs

- Finished face area  $> 101 \text{ in.}^2$  (0.065  $\text{m}^2$ )
- Length divided by thickness  $> 4$
- Minimum thickness of 1.2" (30 mm)
- Maximum length and width of 48" (1220 mm)

#### ASTM C936 Solid Concrete Interlocking Concrete Paving Units

- Finished face area  $> 101 \text{ in.}^2$  (0.065  $\text{m}^2$ )
- Length divided by thickness  $> 4$
- Minimum thickness of 2.36" (60 mm)

#### ASTM A231.1 Precast Concrete Paving Slabs

- Finished face area  $> 139.5 \text{ in.}^2$  (0.09  $\text{m}^2$ )
- Length divided by thickness  $> 4$
- Minimum thickness of 1.2" (30 mm)
- Maximum length and width of 39.3" (1000 mm)

#### ASTM A231.2 Precast Concrete Pavers

- Finished face area  $> 139.5 \text{ in.}^2$  (0.09  $\text{m}^2$ )
- Length divided by thickness  $> 4$
- Minimum thickness of 2.36" (60 mm)

In practical terms, what separates planks from pavers are length and thickness. Shorter and thicker units (pavers) see better performance in vehicular traffic because they aren't as subject to as much bending forces, thereby lowering risk of cracks under tires. A dividing line between planks and pavers is illustrated in the table below with a 3 x 12 x 3.125" thick paving unit. Some might think it's a plank but is not. The unit is a concrete paver that meets C936 and CSA A231.2 definitions.

In addition, its length divided by thickness or aspect ratio is 4, making it acceptable for limited vehicular traffic such as a residential driveway. If the unit was thicker, say 4", the aspect ratio would be 3, thereby capable of accepting parking lot and roadway traffic. In contrast, a 3 x 12" unit with thickness of 2.36" or 60 mm has an aspect ratio of 5, thereby meeting the plank definition. This unit should be used in pedestrian applications only.



## Rochester Concrete Products

### Corporate Office

7200 Broadway Ave. N.  
Rochester, MN 55906  
Phone (507) 288-8850  
Fax (507) 535-1487

[www.rochesterpcp.com](http://www.rochesterpcp.com)

© Copyright 2021, Rochester Concrete Products. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners. Rochester Concrete Products assumes no liability for its accuracy or completeness. Final determination of the suitability of any information or material for the use contemplated, or for its manner of use, is the sole responsibility of the user. PROPOSITION 65 WARNING: These Products, the fuel used in this Products and other wood and charcoal burning appliances, and the combustion products of such fuels contain chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm. 421

