



solid solutions to better hardscapes

PO Box 70 • 32020 126th St • Princeton, MN 55371 • Tel 800-752-9326 • Fax 763-389-2725

70gsm Silt Fence (Commercial)

70gsm Silt Fence meets or exceeds the physical property values listed below.

Fabric Property	Test Method	Units	Minimum Average Roll Value
Grab Tensile	ASTM D 4632	lbs.	65
Elongation	ASTM D 4632	lbs.	18
Trap Tear Strength	ASTM D 4533	lbs.	55
Puncture Resistance	ASTM D 4833	lbs.	40
Mullen Burst	ASTM D 3786	Psi	160
Permittivity	ASTM D 4491	sec ⁻¹	.1
Water Flow	ASTM D 4491	gpm/ft ²	10
UV Resistance	ASTM D 4355	% Strength Retained	80
AOS	ASTM D 4751	US Sieve	40

Values Provided represent expected values at time of manufacture. This document provides the characteristic properties of the product described.

To the best of our knowledge, the information contained herein is accurate. However, SRW Products cannot anticipate all conditions under which SRW product information and our products or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety or suitability of our products either alone or in combination with other products. Final determination of the suitability of any information or material for the use contemplated, or its manner of use, and whether the suggested use infringes any patents is the sole responsibility of the user.

Visit our Website at www.SRWProducts.com • Become a fan and “LIKE” us on Facebook
